Lumicor.

PLEASE CAREFULLY INSPECT ALL LUMICOR PRODUCTS PRIOR TO INSTALLATION. CONTACT LUMICOR AT 1-888-LUMICOR IMMEDIATELY REGARDING ANY DAMAGE OR DEFECT. FAILURE TO DO SO MAY JEOPARDIZE YOUR RIGHTS TO WARRANTY REPLACEMENT AND/OR REIMBURSEMENT FOR SHIPPING DAMAGE.

Lumicor tables are intended for interior use only.

ASSEMBLY

TOOLS NEEDED

- Phillips screwdriver
- 7/32 " Allen wrench (for disc base assembly)

STEPS

- 1. Leave protective masking on topside to prevent scratches or damages during assembly.
- 2. Lay table top face down on a flat, clean surface where you should now see the mounting surface with the four (4) threaded inserts.
- 3. Place 1/4" flat washers over the threaded inserts.
- 4. Locate the assembled table base and flip over to align the threaded inserts in the top with the corresponding holes in the table base plate.

Note: if using disc base, connect bottom disc plate to cylinder post by aligning the two holes and using an Allen wrench to install and tighten screws.

- 5. Install ¼" screws and lock washers with Phillips screwdriver and tighten.
- 6. Turn table upright again and remove protective masking from the table top.

CLEANING

Use warm water, mild soap and a soft sponge or cloth to clean Lumicor. Any acrylic cleaner may also be used. Do not use alcohol, glass cleaners, acetone, lacquer thinner, solvents or abrasive compounds. Do not use squeegees, scrapers or synthetic rags that may scratch the panels. Novus cleaner and polish is an approved product for a clean shine that also protects from static build up. For more information, see the "General Polishing & Basic Scratch Repair" document on our website at www.lumicor.com/ScratchRepair.

HANDLING

Lumicor products ship with a protective masking that should not be removed until assembly is complete, but within 90 days of receipt of order.

NEVER store Lumicor tables in direct sunlight or in extreme temperatures above 100°F (37°C) **NEVER** expose Lumicor products to solvents or solvent vapors. **NEVER** over-tighten through-bolt fasteners. This may cause Lumicor products to crack.

Disclaimer: We believe this information to be reliable and offer the information in good faith without guarantee, as conditions and methods of use are beyond our control. We recommend prospective buyers perform their own testing to determine product suitability for all purposes before adopting Lumicor on a commercial scale. In no case is Lumicor liable for direct, consequential, economic or other damages. Lumicor disclaims all other warranties, expressed or implied, including the warranty of merchantability and fitness for a particular purpose.