

General Polishing & Basic Scratch Repair

Novus #1 Plastic Cleaner and Polish

Gently cleans all Lumicor material without scratching. Leaves a lustrous shine that resists fogging, repels dust, and eliminates static. This is a general purpose, daily use cleaner. Use it on all Lumicor material.

Resists finger marking. Contains no abrasives or harsh chemicals. Leaves a smooth, clean, greaseless shine. If the surface is extremely dirty, apply NOVUS No. 1 liberally and wipe using long, sweeping strokes. Do not use pressure, as large dirt particles may scratch the plastic. Re-apply NOVUS No. 1. Polish using short, circular strokes with a clean portion of the cloth. When surface is thoroughly clean and uniformly covered, buff to a slippery glaze with a clean cloth. Surfaces buffed to a high glaze are more resistant to dust and future scratching. Reapply NOVUS No. 1 regularly to maintain the antistatic, smudge and scratch resistant properties.

Novus #2 Fine Scratch Remover

Removes fine scratches, haziness and abrasions from most Lumiclear, Lumiform and Lumiguard surfaces. With repeated use, NOVUS No. 2 restores faded and discolored areas. Removes the damage instead of filling it in. Buffs out quickly. After restoring, seals with a coat of polish. Observe condition of the surface to be treated. The deeper the scratches, the greater the pressure required to remove them. If the surface is dirty, clean with NOVUS No.1 before applying NOVUS No. 2. Shake well. Test in an inconspicuous area. Apply NOVUS No. 2 liberally. Using a clean, soft cloth, polish with a firm back-and-forth motion at right angles to the scratches. Keep the cloth saturated with polish at all times. When the worst scratches have been polished out, reapply NOVUS No. 2 uniformly in a circular motion to the entire surface using short, circular strokes and light pressure. Allow to dry to a light haze. Using a clean portion of the cloth, buff the surface to a slippery glaze using firm, short strokes. This procedure is imperative in achieving the best results. For heavy scratches, multiple applications of NOVUS No. 2 or application of NOVUS No. 3 may be required. Follow with NOVUS No. 1 for best results.

Novus #3 Heavy Scratch Remover

Removes heavy scratches and abrasions from most Lumiclear, Lumiform and Lumiguard surfaces. Not recommended for use on Chemshield. Use when damage is too severe to be restored with NOVUS No. 2 polish. Requires use of NOVUS No. 2 for final finishing. Shake well. Test in an inconspicuous area. Apply NOVUS No. 3 liberally. Using a clean, soft cloth, polish with a firm back-and-forth motion at right angles to the scratches. Keep the cloth saturated with polish at all times. Continue polishing until only fine scratches remain. Using cloth, remove all remaining polish; this is very important! Using a clean cloth, apply NOVUS No. 2 in a circular motion uniformly to entire surface. Polish using light pressure until NOVUS No. 2 dries to a light haze. Using a clean portion of the cloth, buff the surface clean. Follow with NOVUS No. 1 for best results.

Do

- Use a soft cotton cloth. The type of polishing cloth you use will make a difference. Ideal cloth is nonabrasive, absorbent, and lint free.

Don't

- Reuse cloths. Reusable cloths can retain abrasive particles, but you won't know for sure until the damage is done.

The information and data contained within this document pertain to the properties of Lumicor material only. We believe this information to be reliable, and offer the information in good faith without guarantee, as conditions and methods of use are beyond our control. We recommend prospective buyers perform their own testing to determine suitability of Lumicor for all purposes before adopting Lumicor on a commercial scale. In no case is Lumicor, Inc. liable for direct, consequential, economic, or other damages. Lumicor disclaims all other warranties, expressed or implied, including the warranty of merchantability and fitness for a particular purpose.